

Attachments / Planer

Planer Specifications

Units METRIC

Planer, Standard Flow - 14"

Planer, High Flow - 18"

Planer, High Flow - 24"

Planer, High Flow - 40"

General

	Planer, Standard Flow - 14"	Planer, High Flow - 18"	Planer, High Flow - 24"	Planer, High Flow - 40"
Operating Weight	502 kg	540 kg	569 kg	1043 kg
Length	1206 mm	1206 mm	1206 mm	1118 mm
Width	1687 mm	1687 mm	1687 mm	1727 mm
Height	744 mm	894 mm	894 mm	813 mm
Cutting Depth Max	152 mm	152 mm	152 mm	127 mm
Cutting Depth Min	0 mm	0 mm	0 mm	0 mm
Drum Width Max	356 mm	457 mm	610 mm	1016 mm
Number of Bits	n/a	n/a	n/a	78
Sideshift	757 mm	757 mm	757 mm	650 mm
Maximum Cutting Angle	15°	15°	15°	8°
Planing Distance Next to Curb	1915 mm	1915 mm	2042 mm	66 mm
Drum Diameter	451 mm	451 mm	451 mm	368 mm
Flow Range Min	56.8 l/min	83.3 l/min	83.3 l/min	94.6 l/min
Flow Range Max	102.2 l/min	151.4 l/min	151.4 l/min	223.3 l/min

Compatible Carriers

Skid-Steer Loaders				
Bobcat S62 T4	■	■	■	
Bobcat S64	■	■	■	
Bobcat S66	■	■	■	
Bobcat S76	■	■	■	
Bobcat S450	■			

Bobcat S450	■			
Bobcat S570	■	■	■	
Bobcat S590	■			
Bobcat S650	■	■	■	
Bobcat S740	■	■	■	
Bobcat S770	■	■	■	■
Bobcat S850		■	■	■

Compact Track Loaders				
Bobcat T62	■	■	■	
Bobcat T64	■	■	■	
Bobcat T66	■	■	■	
Bobcat T76	■	■	■	
Bobcat T450	■			
Bobcat T450	■			
Bobcat T550	■			
Bobcat T595	■			
Bobcat T630	■	■	■	
Bobcat T740	■	■	■	
Bobcat T770	■	■	■	■
Bobcat T870		■	■	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.